

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Problem Image Mailbox.**



20 μm

Figure 1

XRD pattern of MM-1 sintered at 500°C




Figure 2

**PCT measurement at 240°C for
MM-1 sintered at 500 °C**




Figure 3

Hydrogen Absorption for Sintered MM-1




Figure 4

Hydrogen Desorption of Sintered MM-1




Figure 5

MM-1 sintered at 570°C and 600°C

Desorption measured at 240°C





Figure 6



20 μm

Figure 7

XRD Spectrum of MM-1




Figure 8

PCT measurement at 240° C for
MA-MM-1 with 100 Å Fe double side coating




Figure 9

PCT measurements for MA-MM-1 with 100Å Fe double side coating





Figure 10



20 μm

Figure 11




Figure 12







Figure 13





20 μm

- 1. Fe-inclusion
- 2. Mg-Al phase
- 3. Mg phase


Figure 14




(a) Surface Coating Method



(b) Mechanical Alloying Method



(c) Sintering Method



(d) Quick Quench Plus Coating

Figure 15